ACCESS µCABLE UP TO 12 FIBRES

Standards reference:

European standards series EN 60794 International standards series IEC 60794

Application / Features

		S	~			Ö	A	**	M
Excellent	•								
Very good								•(1)	
Good		•		•	•	•(1)	•	•(2)	•(2)
Medium			•			•(2)			
Poor									•

- (1) indoor option
- (2) outdoor option

This µCABLE (micro-cable) is proposed with two options:

- Halogen free, flame-retardant indoor option for installation in buildings, laying in trough and blowing in micro-ducts (3);
- Watertight outdoor option for pulling, blowing, air and water-floating in microducts (3).

Due to its structure closed to **Silec Cable** $\mu SHEATH^{@}$ and UNIGAINE[®] designs, this cable is ultra-compact, very light, easy to handle, offer easy entry / fibre access (both cable end and mid-span) and is suitable to both individual and mass-splicing.

(3) maximum distance for blowing depending on the micro-duct (type and size) and on the route configuration..

Fibre count (4)	Weight kg/km	Diameter, mm	Bending radius, mm	Maximum Tensile load - Installation / permanent, daN	Delivery length, km (5)	Environ- ment						
Indoor access µCABLES ≤ 12 O.F.												
<u><</u> 12	16	3.8 +/- 0.2	30	20 / 7	≤5 km	Halogen free & flame- retardant						
Outdoor access µCABLES ≤ 12 O.F.												
<u><</u> 12	13	3.8 +/- 0.2	30	23 / 8	≤5 km	Watertight						

- (4) Other fibre counts possible under request.
- (5) May depend on fibre type used. Please consult us.

Design

- Colour-coded optical fibres, of any type, singlemode (G652, G655,...), or multimode 50/125 or 62.5/125.
- 2. Filling compound.
- 3. PBT loose tube
- 4. Dielectric strength members
- Outer jacket [Indoor option: low smoke, halogen free thermoplastic LSOH -Standard colour: ivory (*) - Outdoor option: PE jacket - Standard colour: black (*)].



Optical fibres are individually coloured according to the following code*: Red, Blue, Green, Yellow, Violet, White, Orange, Slate, Brown, Black, Aqua, Rose.

Outer marking

Year - Fibre count - fibre type - Silec + metric marking

(*) For specific requirements: please contact us.

No reproduction without the written consent of Silec Cable – Silec Cable reserves the right to change the specifications for improvement without notice. Silec trademark is a registred trademark











