


.....

OPTRAL

ABD



Multitube Distribution Cable FTTx



Cable Description

- 01. Central Element (GRP)
- 02. Fibre Optics
- 03. Loose Tubes (Jelly Filled)
- 04. Outer Jacket

Applications

Outdoor

Options

- LSZH Jacket
- PA12 Jacket



Advantages

Compact / Tough / Resistant / Totally Dielectric / Excellent resistance to friction / Suitable for "blow air" systems.



TOTALLY DIELECTRIC



MOISTURE-PROTECTED



LOW FRICTION



ULTRAVIOLET RESISTANCE

All technical specifications are subject to change without prior notice. gor.

SPECIFICATIONS						
Fibre Count	24	36	48	72	96	144
Total Tubes	6	6	6	6	8	12
Active Tubes	2	3	4	6	8	12
Fibres per Tube	12					
Outer Jacket	Polyethylene					
Colour	Black					
Weight (Kg/Km)	29	29	29	29	42	72
Outer Ø (mm)	5.7 ±0.2	5.7 ±0.2	5.7 ±0.2	5.7 ±0.2	6.6 ±0.2	8.6 ±0.2
Tensile Load (N)	500	500	500	500	1200	1500
Temperature Range	-40° C to +70° C					
Min. Bending radius	20 x Outer Ø					

Standards

Environmental and Mechanical tests according to EN 187000 and CEI 60794.

Fibres colour code: red, green, blue, yellow, grey, violet, brown, orange, white, pink, black, natural.

.....